## INSPECTION CHECKLIST FOR

## Jack hammer / pneumatic breaker



(	NAME	DATE	H	AMMER No	
- \					

All the items in the "ITEMS TO BE CHECKED" column must be checked by operators before operating equipment.

Indicate whether each item is in a serviceable condition (using a tick) or not (using a cross). If irrelevant, write n/a in the comments section. If defective, comment on the exact nature of the defect and do not operate until reported and corrected. A new checklist then needs to be filled in and retained.

## PERSONAL PROTECTIVE EQUIPMENT REQUIRMENTS

Overall, eye protection / face shielding, hearing protection, dust mask, safety shoes, anti-vibration gloves



TIEMSTO BE CHECKED  COMPRESSED AIR HOSE & COUPLINGS UNDAMAGED  BREAKER PROPERLY LUBRICATED  BUILT-IN LUBRICATOR FILLED DAILY  OIL PLUG TIGHT  OIL PLUG O-RING UNDAMAGED AND TIGHT-FITTING  TOOL RETAINER DOES NOT RELEASE WHEN CLOSED  TOOL CHUCK NOT WORN; NO EXCESSIVE PLAY  VIBRATION-REDUCING HANDLES (IF APPLICABLE)  HANDLES MOVE FREELY UP & DOWN  NO EXCESSIVE BACKWARD / FORWARD PLAY  SPRRINGS UNDAMAGED  ACCESSORY NOT DULL /ABRADED  MOUNTING SCREWS PROPERLY TIGHTENED  CARBON BRUSHES NOT WORN / DAMAGED  COMPRESSOR AT SUFFICIENT CAPACITY  AIR HOSE  UNDAMAGED  SIZE & LENGTH CORRECT  INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS  NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER  SUITABLE FOR SHANK OF AIR BREAKER
COMPRESSED AIR HOSE & COUPLINGS UNDAMAGED BREAKER PROPERLY LUBRICATED BUILT-IN LUBRICATOR FILLED DAILY OIL PLUG TIGHT OIL PLUG O-RING UNDAMAGED AND TIGHT-FITTING TOOL RETAINER DOES NOT RELEASE WHEN CLOSED TOOL CHUCK NOT WORN; NO EXCESSIVE PLAY VIBRATION-REDUCING HANDLES (IF APPLICABLE) HANDLES MOVE FREELY UP & DOWN NO EXCESSIVE BACKWARD / FORWARD PLAY SPRRINGS UNDAMAGED ACCESSORY NOT DULL / ABRADED MOUNTING SCREWS PROPERLY TIGHTENED CARBON BRUSHES NOT WORN / DAMAGED COMPRESSOR AT SUFFICIENT CAPACITY AIR HOSE UNDAMAGED SIZE & LENGTH CORRECT INTERIOR OF HOSE CLEAN AIR BREAKER NO LOOSENESS IN SCREW THREAD AREAS NO CRACKS / BREAKS IN MAIN BODY CHISEL SUITABLE FOR SHANK OF AIR BREAKER
BUILT-IN LUBRICATOR FILLED DAILY OIL PLUG TIGHT OIL PLUG O-RING UNDAMAGED AND TIGHT-FITTING TOOL RETAINER DOES NOT RELEASE WHEN CLOSED TOOL CHUCK NOT WORN; NO EXCESSIVE PLAY VIBRATION-REDUCING HANDLES (IF APPLICABLE) HANDLES MOVE FREELY UP & DOWN NO EXCESSIVE BACKWARD / FORWARD PLAY SPRRINGS UNDAMAGED ACCESSORY NOT DULL / ABRADED MOUNTING SCREWS PROPERLY TIGHTENED CARBON BRUSHES NOT WORN / DAMAGED COMPRESSOR AT SUFFICIENT CAPACITY AIR HOSE UNDAMAGED SIZE & LENGTH CORRECT INTERIOR OF HOSE CLEAN AIR BREAKER NO LOOSENESS IN SCREW THREAD AREAS NO CRACKS / BREAKS IN MAIN BODY CHISEL SUITABLE FOR SHANK OF AIR BREAKER
OIL PLUG TIGHT OIL PLUG O-RING UNDAMAGED AND TIGHT-FITTING TOOL RETAINER DOES NOT RELEASE WHEN CLOSED TOOL CHUCK NOT WORN; NO EXCESSIVE PLAY VIBRATION-REDUCING HANDLES (IF APPLICABLE) HANDLES MOVE FREELY UP & DOWN NO EXCESSIVE BACKWARD / FORWARD PLAY SPRRINGS UNDAMAGED ACCESSORY NOT DULL / ABRADED MOUNTING SCREWS PROPERLY TIGHTENED CARBON BRUSHES NOT WORN / DAMAGED COMPRESSOR AT SUFFICIENT CAPACITY AIR HOSE UNDAMAGED SIZE & LENGTH CORRECT INTERIOR OF HOSE CLEAN AIR BREAKER NO LOOSENESS IN SCREW THREAD AREAS NO CRACKS / BREAKS IN MAIN BODY CHISEL SUITABLE FOR SHANK OF AIR BREAKER
OIL PLUG O-RING UNDAMAGED AND TIGHT-FITTING TOOL RETAINER DOES NOT RELEASE WHEN CLOSED TOOL CHUCK NOT WORN; NO EXCESSIVE PLAY  VIBRATION-REDUCING HANDLES (IF APPLICABLE)  HANDLES MOVE FREELY UP & DOWN NO EXCESSIVE BACKWARD / FORWARD PLAY  SPRRINGS UNDAMAGED  ACCESSORY NOT DULL / ABRADED  MOUNTING SCREWS PROPERLY TIGHTENED  CARBON BRUSHES NOT WORN / DAMAGED  COMPRESSOR AT SUFFICIENT CAPACITY  AIR HOSE  UNDAMAGED  SIZE & LENGTH CORRECT INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
TOOL RETAINER DOES NOT RELEASE WHEN CLOSED TOOL CHUCK NOT WORN; NO EXCESSIVE PLAY  VIBRATION-REDUCING HANDLES (IF APPLICABLE)  HANDLES MOVE FREELY UP & DOWN NO EXCESSIVE BACKWARD / FORWARD PLAY  SPRRINGS UNDAMAGED ACCESSORY NOT DULL / ABRADED  MOUNTING SCREWS PROPERLY TIGHTENED  CARBON BRUSHES NOT WORN / DAMAGED  COMPRESSOR AT SUFFICIENT CAPACITY  AIR HOSE  UNDAMAGED  SIZE & LENGTH CORRECT INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
TOOL CHUCK NOT WORN; NO EXCESSIVE PLAY  VIBRATION-REDUCING HANDLES (IF APPLICABLE)  HANDLES MOVE FREELY UP & DOWN  NO EXCESSIVE BACKWARD / FORWARD PLAY  SPRRINGS UNDAMAGED  ACCESSORY NOT DULL / ABRADED  MOUNTING SCREWS PROPERLY TIGHTENED  CARBON BRUSHES NOT WORN / DAMAGED  COMPRESSOR AT SUFFICIENT CAPACITY  AIR HOSE  UNDAMAGED  SIZE & LENGTH CORRECT  INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS  NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
VIBRATION-REDUCING HANDLES (IF APPLICABLE)  HANDLES MOVE FREELY UP & DOWN  NO EXCESSIVE BACKWARD / FORWARD PLAY  SPRRINGS UNDAMAGED  ACCESSORY NOT DULL / ABRADED  MOUNTING SCREWS PROPERLY TIGHTENED  CARBON BRUSHES NOT WORN / DAMAGED  COMPRESSOR AT SUFFICIENT CAPACITY  AIR HOSE  UNDAMAGED  SIZE & LENGTH CORRECT  INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS  NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
HANDLES MOVE FREELY UP & DOWN  NO EXCESSIVE BACKWARD / FORWARD PLAY  SPRRINGS UNDAMAGED  ACCESSORY NOT DULL / ABRADED  MOUNTING SCREWS PROPERLY TIGHTENED  CARBON BRUSHES NOT WORN / DAMAGED  COMPRESSOR AT SUFFICIENT CAPACITY  AIR HOSE  UNDAMAGED  SIZE & LENGTH CORRECT  INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS  NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
NO EXCESSIVE BACKWARD / FORWARD PLAY  SPRRINGS UNDAMAGED  ACCESSORY NOT DULL / ABRADED  MOUNTING SCREWS PROPERLY TIGHTENED  CARBON BRUSHES NOT WORN / DAMAGED  COMPRESSOR AT SUFFICIENT CAPACITY  AIR HOSE  UNDAMAGED  SIZE & LENGTH CORRECT  INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS  NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
SPRRINGS UNDAMAGED  ACCESSORY NOT DULL / ABRADED  MOUNTING SCREWS PROPERLY TIGHTENED  CARBON BRUSHES NOT WORN / DAMAGED  COMPRESSOR AT SUFFICIENT CAPACITY  AIR HOSE  UNDAMAGED  SIZE & LENGTH CORRECT  INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS  NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
ACCESSORY NOT DULL / ABRADED  MOUNTING SCREWS PROPERLY TIGHTENED  CARBON BRUSHES NOT WORN / DAMAGED  COMPRESSOR AT SUFFICIENT CAPACITY  AIR HOSE  UNDAMAGED  SIZE & LENGTH CORRECT  INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS  NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
MOUNTING SCREWS PROPERLY TIGHTENED  CARBON BRUSHES NOT WORN / DAMAGED  COMPRESSOR AT SUFFICIENT CAPACITY  AIR HOSE  UNDAMAGED  SIZE & LENGTH CORRECT  INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS  NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
CARBON BRUSHES NOT WORN / DAMAGED  COMPRESSOR AT SUFFICIENT CAPACITY  AIR HOSE  UNDAMAGED  SIZE & LENGTH CORRECT  INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
COMPRESSOR AT SUFFICIENT CAPACITY  AIR HOSE  UNDAMAGED  SIZE & LENGTH CORRECT  INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS  NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
AIR HOSE  UNDAMAGED  SIZE & LENGTH CORRECT  INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS  NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
UNDAMAGED  SIZE & LENGTH CORRECT  INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS  NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
SIZE & LENGTH CORRECT INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
INTERIOR OF HOSE CLEAN  AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS  NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
AIR BREAKER  NO LOOSENESS IN SCREW THREAD AREAS  NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
NO LOOSENESS IN SCREW THREAD AREAS NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
NO CRACKS / BREAKS IN MAIN BODY  CHISEL  SUITABLE FOR SHANK OF AIR BREAKER
CHISEL SUITABLE FOR SHANK OF AIR BREAKER
SUITABLE FOR SHANK OF AIR BREAKER
SUITABLE FOR WORK
NO WEAR / CRACKS
MOUNTED CORRECTLY
AIR SUPPLY PRESSURE SUITABLE

OPERATOR SIGNATURE DATE	
-------------------------	--

Never use equipment you're not trained to operate Contact us at +27 (0) 12 661 6721 or visit us at www.hretd.co.za for quality in-service training